The Spruce, Drab and Yellow JAP-A-LAC are the solid colors, and are much more preferable to any Floor Paint on the market, being far more durable.

When used on the wire cloth of Window Screens, the Brilliant Black JAP-A-LAC should be used after having thinned same down from 1/3 to 1/2 with Turpentine. The Mahogany, Oak, Cherry or Walnut IAP-A-LAC should be applied full strength on the frames or wooden parts of Window Screens. By so doing it will double their life and make them look as good as new.

JAP-A-LAC should not be substituted for, or confounded with, the ordinary Varnish Stains, as its purpose is entirely different.

Insist on getting JAP-A-LAC at your Paint Dealers, and if you cannot get it, send to us direct, but don't take any substitute.

The Glidden Varnish Co.,

Cleveland, Ohio, U. S. A.

TAP-A-LAC dries with an elasticity and hardness of Japanese Lacquer, and is much cheaper and more hygienic than carpets when used on floors, and with rugs or matting; gives a room an air of refinement.

PRICES AND COVERING QUALITIES.

1 gallon can	\$2.50	cover	s 300	sq. feet :	2 coats
1/2 " 150	1.35	"	150	"	"
Quart can	75		75,	66	"
Pint can. 50	40	"	38	"	**
1/2 pint can 3.0.	25	- 66	18	- "	44
5 gallon cans @ \$			lon.	(Natura	d only

FOR SALE BY

NOTICE.

The same good qualities that make JAP-A-LAC the best Floor Varnish or Finish, should also make it the very best Finish for all kinds of interior woodwork. Architects, builders and painters "stop to think," and act as your best judgment tells you.




FOR SALE BY

TALBOT & HUBBARD. HARDWARE

Phoenix. - Arizona





Floors It is the best and most durable finish ever used on either hard or soft wood floors.

Front Doors: Weather-beaten doors look like new when coated with Jap-a-lac. It re-

sists the sun and moisture.

Wood Work, Furniture, etc., which has become marred, scratched and worn, coated

with Jap-a-lac is renewed and beautified.

Screens: Brilliant Black Jap-a-lac beautifies and prolongs the life of wire cloth on screens, and the Mahogany, Cherry or Walnut Jap-a-lac used on the frames makes them look as good as new.

Wicker-Furniture coated with Mahogany, Oxblood Red, Cherry or Mala-

chite Green Jap-a-lac looks better than new.

Old Carriages coated with Brilliant Black Jap-alac are renewed and given new life. Refrigerators, Kitchen Sinks, Wainscoating, etc., finished with Jap-a-lac resist mois-

ture and are given a beautiful and durable finish. Iron Fences, Wire Screens, Radiators, Registers, Water Pipes, Hot Water Tanks, etc., coated with black or Spruce Jap-a-lac always lookwell. Porch Furniture coated with Jap-a-lac is renewed and beautified and a lasting and

durable finish is obtained.

Linoleum and Oil Cloths finished with Natural or Clear Jap-a-lac look better than new and resist soap and water, thereby promoting the life of same

Bar Tops and Counter Tops coated with Jap-a-lac are renewed with a lasting and durable

Note: One coat of Dead Black Jap-a-lac applied on tarnished Chandeliers, Picture Frames, Fire Fronts, Lamps, etc., produces the new artistic Black Wrought Iron Finish which is so popular.

" EASILY APPLIED AND QUICKLY DRIED."

"WEARS LIKE IRON."



EASILY APPLIED. OUICKLY DRIED."

SPECIAL DIRECTIONS FOR USING JAP-A-LAC

IAP-A-LAC stains and varnishes by one application, and is beyond doubt the most durable Floor Finish on the market; also best possible Finish for all kinds of Interior Woodwork, where extreme durability is required.

It is the greatest revivor of old woodwork ever offered to the public, for it covers up all mars, scratches or disfigurements, producing a brilliant and beautiful finish, and can be applied by an inexperienced person. It is not affected by hot or cold water, nor by soap and water, and does not mar white or show heel marks when used on floors.

If found too heavy to work easily, thin with a little Turpentine by stirring it in thoroughly.

Open-grain woods, such as Oak, Ash, etc., which have not been previously coated, should first be filled with a good paste filler and allowed from 24 to 36 hours to dry before applying JAP-A-LAC.

Old Floors and woodwork should first be washed with Sapolio and water to remove any dirt or grease, and allowed to dry before finishing. Apply at least two coats on work which has not been previously finished, allowing sufficient time for the first coat to harden.

Should you wish to obtain the Oak effect on an old Floor, give it a coat of the Yellow JAP-A-LAC (Solid Color), allowing it to dry, and then apply a coat of Oak JAP-A-LAC over same.

In re-finishing old woodwork, it is well to use the color nearest that of the old finish unless you wish to change the color, which may be done by applying sufficient number of coats to cover properly, allowing from 24 to 36 hours between coats.

The Mahogany, Walnut, Cherry or Oak JAP-A-LAC applied on weather-beaten Front Doors has the same effect as polishing an old pair of rusty shoes.

NO HOME IS COMPLETE WITHOUT JAP-A-LAC."